

WIRE ROPE SPELTER SOCKET

WIRE ROPE SPELTER SOCKET – OPEN TYPE

Product Code: CA-0106

Nominal Size of Rope		Dimension (mm)								Weight (kgs)
(mm)	(Inch)	A	B	C	D	E	F	G	d	
16 – 20	$5/8 - 13/16$	219	88	39	82	36	63	24	31	3.6
22 – 26	$7/8 - 1$	270	107	50	103	47	81	31	41	7.2
28 – 32	$1 1/8 - 1 1/4$	322	126	61	124	57	99	38	50	18
34 – 38	$1 5/16 - 1 1/2$	368	145	72	138	66	115	44	59	24
40 – 42	$1 9/16 - 1 5/8$	413	165	76	142	76	146	48	76	32
44 – 48	$1 3/4 - 1 7/8$	464	178	89	169	79	165	52	89	40
50 – 54	$2 - 2 1/8$	547	229	102	200	96	178	60	95	58
56 – 60	$2 1/4 - 2 3/8$	597	254	114	222	102	197	66	108	77
62 – 66	$2 1/2 - 2 5/8$	648	273	127	247	114	216	76	120	104
70 – 74	$2 3/4 - 2 7/8$	691	279	133	279	124	229	80	127	142
76 – 80	$3 - 3 1/8$	737	286	146	298	133	241	86	133	167

Remark: 1. Material : Cast Alloy Steel. 4. Standard : comply with ISO 3189 requirement.
 2. Finishing : Blasting and Hot Dip Galvanized. 5. Proved by Prototype Testing.
 3. 100% Proof Load (40% of MBL of Rope). 6. Socketing Procedure as request.



Open Type

